



# HOS BLACKHAWK

## HOSMAX280 Offshore Supply Vessel



### DIMENSIONS AND REGULATORY INFORMATION

<b>Length:</b>	280 ft 0 in (85.3 m)	<b>Beam:</b>	60 ft 0 in (18.3 m)	<b>Draft Max:</b>	19 ft 3 in (5.87 m)
<b>Gross:</b>	2,994 GT	<b>Net:</b>	1,148 NT	<b>Draft Min:</b>	10 ft 3 in (3.12 m)
<b>IMO:</b>	9382877	<b>O.N.:</b>	1185543	<b>Flag:</b>	U.S.
<b>Certifications:</b>	Oceans-SOLAS, USCG Subchapter I, USCG Subchapter L				
<b>Classifications:</b>	Loadline, American Bureau of Shipping, +DPS-2, (E), +A1, +AMS, +ACC, ACP, UWILD, OSR-C2				

### PERFORMANCE

<b>Cruise Speed:</b>	10.0 kts	145 gal/hr (549 l/hr)	<b>Max Speed:</b>	12.7 kts	290 gal/hr (1,098 l/hr)
----------------------	----------	-----------------------	-------------------	----------	-------------------------

### PROPULSION, MACHINERY AND STEERING

<b>Main Engines:</b>	2 x Caterpillar 3608	<b>Total Horsepower:</b>	6,598 bhp
<b>Propellers:</b>	CPP, High Efficiency, 4-Blade	<b>Propeller Diameter:</b>	106 in (2,692 mm)
<b>Primary Generators:</b>	2 x Caterpillar 3508B	<b>Total Rating:</b>	1,820 kW
<b>Shaft Generators:</b>	2 x Kato	<b>Total Rating:</b>	4,000 kW
<b>Aft Bow Thruster:</b>	1 x Rolls Royce Swing-down Azimuth	<b>Total Rating:</b>	1,200 hp
<b>Fwd Bow Thruster:</b>	1 x Brunvoll CPP Tunnel	<b>Total Rating:</b>	1,582 hp
<b>Stern Thruster:</b>	1 x Brunvoll CPP Tunnel	<b>Total Rating:</b>	1,582 hp
<b>Rudder:</b>	High Lift, Independent Steering	<b>Power Generation:</b>	480V/60 Hz/3-Phase

### CAPACITIES AND DELIVERY RATES

<b>Deadweight:</b>	4,765 LT (4,841 MT)	<b>Deck Area:</b>	201 ft x 50 ft (10,151 ft <sup>2</sup> )
<b>Deck Cargo:</b>	2,550 LT (2,591 MT)		61.3 m x 15.2 m (943.0 m <sup>2</sup> )
<b>Dry Bulk:</b>	11,440 ft <sup>3</sup> (324 m <sup>3</sup> )	<b>Deck Load Rating:</b>	1,200 lbs/ft <sup>2</sup> (6 MT/m <sup>2</sup> )
<b>Liquid Mud:</b>	15,415 bbl (2,451 m <sup>3</sup> )	<b>System Pressure:</b>	80 psi (5.5 bar)
<b>Potable Water:</b>	34,820 gal (132 m <sup>3</sup> )	<b>Discharge Rate:</b>	1,100 GPM (250 m <sup>3</sup> /hr)
<b>Rig Fuel:</b>	340,679 gal (1,289 m <sup>3</sup> )	<b>Discharge Rate:</b>	1,400 GPM (318 m <sup>3</sup> /hr)
<b>Rig Water:</b>	197,106 gal (746 m <sup>3</sup> )	<b>Discharge Rate:</b>	1,400 GPM (318 m <sup>3</sup> /hr)
<b>Cooler Area:</b>	560 ft <sup>3</sup> (16 m <sup>3</sup> )	<b>Freezer Area:</b>	525 ft <sup>3</sup> (15 m <sup>3</sup> )

### ELECTRONICS

AIS, Auto Pilot, C-Nav, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radascan, S-band Radar, SARTs, Speed Log, SSAS, VHF Radio, VHF Radio (Handheld), VSAT, Windbird, X-band Radar

### ACCOMMODATIONS

12 air conditioned/heated staterooms certified for 29 person berthing.

### SPECIAL FEATURES

<b>Oil Spill Recovery:</b>	ABS Capability Class 2	<b>Recovered Oil Capacity:</b>	15,415 bbl (2,451 m <sup>3</sup> ) (>60 °C FP)
<b>Deck Crane:</b>	1 x North Pacific MCF-530	<b>Max Lift @ Max Radius:</b>	1.4 MT @ 30 ft
<b>Roll Damping:</b>	Anti-Roll Tank, Passive		

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.