




HOS MAUSER

HOSMAX280 Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	280 ft 0 in (85.3 m)	Beam:	60 ft 0 in (18.3 m)	Draft Max:	19 ft 3 in (5.87 m)
Gross:	2,998 GT	Net:	1,101 NT	Draft Min:	10 ft 3 in (3.12 m)
IMO:	9515852	O.N.:	1211932	Flag:	U.S.
Certifications:	Oceans-SOLAS, USCG Subchapter L, USCG Subchapter I				
Classifications:	Loadline, American Bureau of Shipping, +DPS-2, (E), +A1, +AMS, ACP, OSR-C2, +ACC				

PERFORMANCE

Cruise Speed:	10.0 kts	145 gal/hr (549 l/hr)	Max Speed:	12.7 kts	290 gal/hr (1,098 l/hr)
----------------------	----------	-----------------------	-------------------	----------	-------------------------

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar C280-8	Total Horsepower:	7,200 bhp
Propellers:	CPP, High Efficiency, 4-Blade	Propeller Diameter:	106 in (2,692 mm)
Primary Generators:	2 x Caterpillar C 32	Total Rating:	1,820 kW
Shaft Generators:	2 x Kato	Total Rating:	4,000 kW
Aft Bow Thruster:	1 x Rolls Royce Swing-down Azimuth	Total Rating:	1,100 hp
Fwd Bow Thruster:	1 x Brunvoll CPP Tunnel	Total Rating:	1,700 hp
Stern Thruster:	1 x Brunvoll CPP Tunnel	Total Rating:	1,700 hp
Rudder:	High Lift, Independent Steering	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	4,638 LT (4,712 MT)	Deck Area:	124 ft x 50 ft (6,262 ft ²) 37.8 m x 15.4 m (582 m ²)
Deck Cargo:	2,230 LT (2,265 MT)	Deck Load Rating:	1,200 lbs/ft ² (6 MT/m ²)
Dry Bulk:	12,000 ft ³ (340 m ³)	System Pressure:	80 psi (5.5 bar)
Liquid Mud:	10,232 bbl (1,627 m ³)	Discharge Rate:	1,100 GPM (250 m ³ /hr)
Potable Water:	32,808 gal (124 m ³)	Watermaker Cap.:	4,000 USG/day (15 m ³ /day)
Rig Fuel:	290,971 gal (1,101 m ³)	Discharge Rate:	1,400 GPM (318 m ³ /hr)
Rig Water:	332,907 gal (1,260 m ³)	Discharge Rate:	1,400 GPM (318 m ³ /hr)
Cooler Area:	560 ft ³ (16 m ³)	Freezer Area:	525 ft ³ (15 m ³)

ELECTRONICS

AIS, Auto Pilot, C-Nav, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radascan, S-band Radar, SARTs, Speed Log, SSAS, VHF Radio, VHF Radio (Handheld), VSAT, Windbird, X-band Radar

ACCOMMODATIONS

14 air conditioned/heated staterooms certified for 39 person berthing. The rooms are configured as followed:

1 air-conditioned staterooms for 1 person(s) berthing each

7 air-conditioned staterooms for 2 person(s) berthing each

6 air-conditioned staterooms for 4 person(s) berthing each

Accommodations Includes: 2 Conference Rooms, Laundry, Sick bay, Theater, Lounge

SPECIAL FEATURES

Oil Spill Recovery:	ABS Capability Class 2	Recovered Oil Capacity:	10,232 bbl (1,627 m ³) (>60 °C FP)
Deck Crane:	1 x North Pacific MCF-530	Max Lift @ Max Radius:	1.4 MT @ 30 ft
Roll Damping:	Anti-Roll Tank, Passive		

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.